



Declaration of Performance

No. SSS_DOP_01



- Unique identification code on the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0.5\%$ _ GroupBla
- Intended use(s)
For internal and external _ walls and floorings
- Name or registered trade mark, and contact address for the manufacturer
Söğütseren Seramik A.Ş.
! Erenler Mh. Benzinlik ve Sanayi Cd. No:49 Kurşunlu, Çankırı, Türkiye
! Kayhan Mh. Ertuğrulgazi Cd. No : 91/A Söğüt, Bilecik, Türkiye
www.rino.com.tr
- System(s) of assessment and verification of constancy of performance
System 4
- Name and identification number of notified laboratory, if relevant:
None

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} / A1	EN 14411:2013
Release of dangerous substance, for: - Cadmium - Lead	NPD NPD	
Breaking strength	>700 N for thickness < 7,5mm >1300 N for thickness ≥7,5mm	
Slipperiness	See technical documents and catalogues.	
Tactility	NPD	
Bond strength/adhesion, for: Cementitious adhesive, type C1	≥ 0,5 N/mm ²	
Thermal shock resistance	Pass	
Durability for: - Internal use - External use: freeze-thaw resistance	Pass Pass	

The performance of the product identified in point 1. is in conformity with the declared performance in point 6.
This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

İstanbul, 15.02.2017

Place and date of issue

Hayati Ulukaya - President Ceramics and Porcelain Stoneware Group

Name and function

Signature



Declaration of Performance

No. SSS_DOP_02



1. Unique identification code on the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $0.5\% < E_p \leq 3\%$ _ GroupBIb
2. Intended use(s)
For internal and external _ walls and floorings
3. Name or registered trade mark, and contact address for the manufacturer
Söğütseren Seramik A.Ş.
Kayhan Mh. Ertuğrulgazi Cd. No : 91/A Söğüt 11600, Bilecik, Türkiye
www.rino.com.tr
4. System(s) of assessment and verification of constancy of performance
System 4
5. Name and identification number of notified laboratory, if relevant:
None

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} / A1	EN 14411:2013
Release of dangerous substance, for: - Cadmium - Lead	NPD NPD	
Breaking strength	>700 N for thickness < 7,5mm >1300 N for thickness ≥7.5mm	
Slipperiness	See technical documents and catalogues.	
Tactility	NPD	
Bond strength/adhesion, for: Cementitious adhesive, type C1	≥0,5 N/mm ²	
Thermal shock resistance	Pass	
Durability for: - Internal use - External use: freeze-thaw resistance	Pass Pass	

The performance of the product identified in point 1. is in conformity with the declared performance in point 6.
This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Istanbul, 15.02.2017

Place and date of issue

Hayati Ulukaya - President Ceramics and Porcelain Stoneware Group

Name and function

Signature



Declaration of Performance

No. SSS_DOP_03



1. Unique identification code on the product type
Type, batch or serial number or any other element allowing identification of the product.
Dry-pressed ceramic tiles, with water absorption $E_b > 10\%$ _ GroupBIII
2. Intended use(s)
For internal walls
3. Name or registered trade mark, and contact address for the manufacturer
Söğütseren Seramik A.Ş.
Kayhan Mh. Ertuğrulgazi Cd. No : 91/A Söğüt 11600, Bilecik, Türkiye
www.rino.com.tr
4. System(s) of assessment and verification of constancy of performance
System 4
5. Name and identification number of notified laboratory, if relevant:
None

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} / A1	EN 14411:2013
Release of dangerous substance, for: - Cadmium - Lead	NPD NPD	
Breaking strength	>200 N for thickness < 7,5mm >600 N for thickness ≥7,5mm	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for: Cementitious adhesive, type C1	≥0,5 N/mm ²	
Thermal shock resistance	Pass	
Durability for: - Internal use	Pass	

The performance of the product identified in point 1. is in conformity with the declared performance in point 6.
This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Istanbul, 15.02.2017

Place and date of issue

Hayati Ulukaya - President Ceramics and Porcelain Stoneware Group

Name and function

Signature