

DECLARATION OF PERFORMANCE

Document No : SSS DOP 04

1- Description Of The Product:

Dry-pressed Glazed and Unglazed Porcelain Tiles with Low
Water Absorption- Eb≤0,5 % EN 14411:2016 Annex-G (GL-UGL) Group Bla

2- Intended Use : Porcelain Tiles for Interior and Exterior, Floor

2- Name and Contact Adress of the Manufacturer:

Söğütsen Seramik Sanayi İnşaat Madencilik İthalat İhracat A.Ş
Erenler Mah. Benzinlik ve Sanayi Bölgesi No :49 Kurşunlu/Çankırı/Türkiye

4- Classification: Sistem 4

5- Declared Performance :

TECHNICAL CHARACTERISTICS	PERFORMANCE	RELATED STANDARD
Reaction of Fire	A1 _{FL}	TS-EN 14411:2016
Release of Dangerous Substances, for; -Lead -Cadmium -Other	NPD NPD	TS-EN 14411:2016
Breaking Strength	Thickness ≥7,5mm >1300 N Thickness < 7,5mm > 700 N	TS-EN 14411:2016
Bond strength/Adhesion, for; -Cementitious Adhesives	≥0,5 N/mm ²	TS-EN 14411:2016
Resistance to Slipping-Anti Slipping	NPD	CEN TS 16165
Thermal Shock Resistance	Pass	TS-EN 14411:2016
Durability; - For indoor uses - For outdoor uses (Freeze-Thaw resistance)	Pass Pass	TS-EN 14411:2016
Sensibility	NPD	CEN/TS 15209

The performance of the product identified in point 1 is in camformity with, the declared performance in point 5.
This declaration of performance is issued under the sale responsibility of the manufacturer identified in point 3.

(Regulation ((EU)305/2011)

Signed on behalf of the manufacturer by

Şerafettin AŞIK
Ceramics Group President

Kurşunlu/Çankırı/Türkiye

14.11.2022